



Terminal Professional

3720

- ▶ Approvable class III up to 10.000 e or not approvable
- ▶ Weighing range up to 100,000 kg
- ▶ Protection class IP 65
- ▶ Backlit LC display, character height: 16 m
- ▶ Easylog data set
- ▶ Integrated RS 232 interface and print function
- ▶ Incl. wall bracket / stand bracket



Features

- ▶ Approvable class III up to 10.000 e or not approvable
- ▶ Weighing range up to 100,000 kg
- ▶ Protection class IP 65
- ▶ Backlit LC display, character height: 16 mm
- ▶ 12-key operator control with user-programmable function key
- ▶ Dimensions: 270 x 85 x 58 mm
- ▶ Scale weight: 0.4 kg
- ▶ Functions: Weighing, taring, counting, count check, checking, PLU checking, totaling, order picking, recipe measuring, dosing, neutral measuring, percent weighing, plus / minus / weighing, adding, GLP protocol
- ▶ PLU memory for unit weights, count check, tare and recipe values
- ▶ Easylog data set
- ▶ Integrated RS 232 interface and print function
- ▶ Power supply mode: 100 – 240 V / 50 – 60 Hz
- ▶ Incl. wall bracket / stand bracket
- ▶ Second scale can be connected to second measurement location (not retrofittable)

Products

Ordernumber Variation	Approvable	Model	Protection class	Dimensions (mm)
3720.01.101 Terminal Professional	Yes	Cable output at top	IP 65	270×85×58mm
3720.50.101 Terminal Professional	Yes	Cable output at bottom	IP 65	270×85×58mm